# CERTIFICATE

Issued to: Applicant:

Foshan Shunde Ojun Electrical Co., Ltd. ChengZiLi Industrial Area, HongQi Zhong Road RongGui Avenue, Shunde Area FOSHAN CITY, GUANGDONG, China

Manufacturer/Licensee:

Foshan Shunde Ojun Electrical Co., Ltd. ChengZiLi Industrial Area, HongQi Zhong Road RongGui Avenue, Shunde Area FOSHAN CITY, GUANGDONG, China

**Products** flexible cord switches

**OJUN** Trade name Type/model 8s.303

The product and any acceptable variation thereto is specified in the Annex to this certificate and the documents therein referred to.

DEKRA hereby declares that the above-mentioned product has been certified on the basis of

- a type test according to the standard EN 61058-1:2002 + A2:2008; EN 61058-2-1:2011
- an inspection of the production location according to CENELEC Operational Document CIG 021
- a certification agreement with the number 2100620

DEKRA hereby grants the right to use the ENEC KEMA-KEUR certification mark

The ENEC KEMA-KEUR certification mark may be applied to the product as specified in this certificate for the duration of the ENEC KEMA-KEUR certification agreement and under the conditions of the ENEC KEMA-KEUR certification agreement.

This certificate is issued on: 14 June 2013 and expires upon withdrawal of one of the above mentioned standards.

Certificate number: 2163323.01

DEKRA Certification B.V.

drs. G.J. Zoetbrood Managing Director

H.R.M. Barends Certification Manager

© Integral publication of this certificate is allowed

ACCREDITED BY THE DUTCH COUNCIL FOR ACCREDITATION









ANNEX TO ENEC KEMA-KEUR CERTIFICATE 2163323.01

page 1 of 1

#### SPECIFICATION OF THE CERTIFIED PRODUCT

**Product data** 

product : flexible cord switches

trade name : OJUN type : 8s.303

type reference : common type (C.T.)

pattern no. : 1

circuit to be controlled : resistive and tungsten filament lamp

temperature limit : T55

contact opening : full disconnection frequency of operation : 10.000 operating cycles class : for class II appliances

degree of protection : IP20 degree of pollution : 2

insulating material : tracking resistant 175 V

category to heat and fire : 650°C rated impulse withstand voltage : 2500 V material group : Illa

design : non-rewirable

termination : soldered connections

applied flexible cord : H03VVH2-F 2 x 0,5 mm² and 2 x 0,75 mm²

certification mark : KEMA-KEUR

description : body and actuating member of thermoplastic material

markings : printed on the body

#### **TESTS**

Test requirements

EN 61058-1:2002 + A2:2008

EN 61058-2-1:2011

### **Test result**

The test results are laid down in DEKRA test file 2163323.01.

## Conclusion

The examination proved that all test requirements were met.

Tested by : J. He

Checked by : J.C. Hendriksen

## **Factory location**

Foshan Shunde Ojun Electrical Co., Ltd.,

ChengZiLi Industrial Area, HongQi Zhong Road, RongGui Avenue, Shunde Area,

FOSHAN CITY, GUANGDONG, China